

CARTRIDGE FIXING TOOLS

This TBT must not be used as a substitute for the formal training in the use of cartridge fixing tools. It should serve only as a reminder of training previously received. In appropriate circumstances, the safe use of the equipment being discussed should be demonstrated.

- 1. Only use a cartridge fixing tool if you have been trained and authorised to do so.
- 2. Read manufacturer's instructions carefully.
- 3. Before handling the tool, make sure it is not loaded.
- 4. Load the tool with the barrel pointing away from you, but not towards another person.
- 5. Never place your hand over the end of the barrel.
- 6. Never walk around with the tool loaded load it where you are going to use it.
- 7. Check material into which the pin is to be fired ensure that it is satisfactory and the pin is correct for the material.
- 8. Allow at least 76 mm. (3 ins.) from the edge of the concrete or brickwork.
- 9. Hold the tool at right angles to the surface when firing.
- 10. Wear high impact resistant eye protection, category B.



- 11. In appropriate circumstances, e.g. in enclosed areas and confined spaces, wear ear protection.
- 12. In the event of a misfire, wait one minute before unloading.
- 13. Never leave the tool loaded when not in use.

CRAVEN HR SERVICES

CRAVEN SAFETY SERVICES

CRAVEN ENVIRONMENTAL SERVICES

- 14. Do not leave the tool or unused cartridges lying around at the work place.
- 15. Ensure that the tool and all unused cartridges are returned to a secure storage place after use.
- 16. Remember this tool could kill, always treat it with respect.
- 17. Report any defect in the equipment or the system of work without delay, and do not use.