

Tel: 01756 860 600 info@cravenconsultancyservices.co.uk www.cravenconsultancyservices.co.uk

CIRCULAR SAWS - BENCH

This TBT must not be used as a substitute for formal training in the use of bench circular saws. It should serve only as a reminder of training previously received. In appropriate circumstances, the safe use of the equipment being discussed should be demonstrated.

- 1. Bench circular saws can only be operated by persons who have been trained and authorised to do so.
- 2. All adjustments and cleaning operations must be done with the machine's electricity supply locked off.
- 3. The nose guard must be adjusted as close as possible to the timber being cut.
- 4. Clearance between the front edge of the riving knife and the saw teeth must not exceed 12 mm (½ in) at bench level.
- 5. The top guard must extend below the roots of the teeth in the saw blade.
- 6. A push stick must be used for cuts less than 300 mm (12 in) and for the last 300 mm (12 in) of longer cuts.
- 7. Whenever practicable the fence should be used.
- 8. Always use a brush to clear waste from saw bench, but <u>only</u> when the blade is stationary.
- 9. Long and/or wide lengths of timber must be well supported during cutting.



Tel: 01756 860 600 info@cravenconsultancyservices.co.uk www.cravenconsultancyservices.co.uk

- 10. Extra care is required when thin timber is being cut.
- 11. Always have hair tied back, and wear clothes with no loose sleeves or a long coat which may become entangled in the machine.
- 12. Keep the area free of off-cuts and sawdust.
- 13. Keep all guards in place.
- 14. Report any defect in the equipment or the system of work, and stop work immediately.